



## Specifications Model: C16S

<b>System</b>	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
<b>Image Capture</b>	Image sensor	1/2.9inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux(color mode),0Lux(B&W mode)
	Lens	4mm@F2.1
	View Angle	91.7°(Diagonal)
	Nightvision	Dual Filter,IR-Cut, 2pcs 850nm SMD IR LED, IR irradiation distance:10~15m
<b>Video</b>	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、Saturation、Hue
<b>Audio</b>	N/A	
<b>Network</b>	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Memory</b>	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
<b>Alarm</b>	Alarm Trigger	Motion detection
<b>Physical Environmental</b>	Rated voltage	DC12V±5%
	Power consumption	Related power:6W(IR on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	176*166*110mm(L×W×H)