



## Specifications Model: C22Q

<b>System</b>	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
<b>Image Capture</b>	Image sensor	1/3inch 4M Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	Lens	4.0mm@F2.0
	View Angle	89.4° (diagonal)
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm SMD IR LED IR irradiation distance:5~10m
<b>Video</b>	Encode format	H264, Baseline/Main Profile/High Profile; H.265 Main Profile
	Three Stream	Main Stream: 2560×1440@15fps Sub Stream: 360p(640X360)@15fps Third Stream: 180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
<b>Audio</b>	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
<b>Network</b>	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n/ac
	Wireless LAN Frequency	2.4~2.4835GHz; 5.725~5.850GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
<b>Pan-tilt</b>	Pan-tilt	Pan: 330°,tilt: 110°
	Preset position	PC APP: support 16 positions, phone APP:support 5 positions
<b>Memory</b>	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
<b>Alarm</b>	Alarm Trigger	Motion detection
<b>Physical Environmental</b>	Rated voltage	DC 5V±5%
	Power consumption	Rated power:2.35 W(IR LED on), Maximum Power: 5.40W (Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	110mm X 110mm X 175mm mm(L×W×H)