

Specifications Model: C33-X4

| | | |
|-------------------------------|------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/4 inch 720p Progressive Scan CMOS |
| | Minimum Illumination | 0.3~0.5Lux (Color mode) ,0Lux (B&W mode) |
| | Lens | 2.8~12mm@F1.4 electronic optical Zoom+Focus |
| | View Angle | Support Zoom and Focus synchronously, FOV: 73~23.4°/horizontal, 87.6~27.8°/diagonal |
| | Night vision | Dual Filter,IR-Cut,22pcs 850nm Φ5mm IR LED, IR irradiation distance:8~15m |
| Video | Encode format | H.264 main profile@level:4.0/Motion-JPEG/JPEG |
| | Three Stream | Main Stream:720p(1280X720)@25fps Sub Stream:360p(640X360)@25fps Third Stream:180p(320X180)@10fps |
| | Bit Rate | 128~4096kbps |
| | Maximum frame rate | 25fps |
| | Image adjustment | Contrast、Brightness、 Saturation、 Hue |
| | Audio | N/A |
| Network | Ethernet | 10Base-T / 100Base-TX, RJ45 connector |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc |
| | Wireless LAN | IEEE802.11b/g/n |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan-tilt | Pan-tilt | Pan: 355°,tilt: 90° |
| | Preset position | PC APP: support 16 positions, Phone APP:support 5 positions |
| Memory | Socket | TF Push-push socket,Maximum support 128GB; Cloud Storage |
| Alarm | Alarm Trigger | Motion detection |
| Physical Environmental | Rated voltage | DC 5V±5% |
| | Power consumption | Related power:3.5W(IR LED on), Maximum power: 7W (Pan&Tilt&Zoom on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Gross: 1688g(Note: in kind prevail) |
| | Package size | 253*163*266mm (L×W×H) |