



## Specifications Model: C34S-X4

|                               |                        |   |
|-------------------------------|------------------------|---|
| <b>System</b>                 | Operation system       | Embedded Linux OS   |
|                               | Online visitor         | Support 4 visitors at the same time   |
| <b>Image Capture</b>          | Image sensor           | 1/2.7 inch1080p Progressive Scan CMOS   |
|                               | Minimum Illumination   | 0.5Lux (Color mode) ,0.1Lux (B&W mode)  |
|                               | Lens                   | <a href="#">2.8~12mm@F1.4</a> electronic optical Zoom+Focus   |
|                               | View Angle             | Support Zoom and Focus synchronously,<br>FOV: 103° ~30.8°/horizontal, 74.4° ~23.3°/vertical, 130° ~40°/diagonal |
|                               | Night vision           | Dual Filter,IR-Cut,6pcs 850nm Φ5mm IR LED,<br>IR irradiation distance:30m                                       |
| <b>Video</b>                  | Encode format          | H.264 main profile@level:4.0/Motion-JPEG/JPEG   |
|                               | Three Stream           | Main Stream:1080p(1920X1080)@15fps<br>Sub Stream:360p(640X360)@15fps<br>Third Stream:180p(320X180)@10fps        |
|                               | Bit Rate               | 128~4096kbps  |
|                               | Maximum frame rate     | 15fps   |
|                               | Image adjustment       | Contrast、Brightness、Saturation、Hue  |
| <b>Audio</b>                  | N/A                    | N/A   |
| <b>Network</b>                | Ethernet               | 10Base-T / 100Base-TX, RJ45 connector   |
|                               | Protocols              | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc   |
|                               | Wireless LAN           | IEEE802.11b/g/n   |
|                               | Wireless LAN Frequency | 2.4~ 2.4835GHz  |
|                               | Wireless LAN security  | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption  |
| <b>Pan-tilt</b>               | Pan-tilt               | Pan: 355°,tilt: 90°   |
|                               | Preset position        | PC APP: support 16 positions, Phone APP:support 5 positions   |
| <b>Memory</b>                 | Socket                 | TF Push-push socket,Maximum support 128GB; Cloud Storage  |
| <b>Alarm</b>                  | Alarm Trigger          | Motion detection  |
| <b>Physical Environmental</b> | Rated voltage          | DC 12V±5%   |
|                               | Power consumption      | Related power:6.72W(IR LED on), Maximum power: 16.32W (Pan&Tilt&Zoom on)  |
|                               | Operating condition    | Temperature:-10~50℃,humidity:<90%   |
|                               | Weight                 | Gross: 1555g(Note: in kind prevail)   |
|                               | Package size           | 250*163*262mm (L×W×H)   |