



Specifications Model: C35

| | | |
|-------------------------------|----------------------------|---|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/4 inch 720p Progressive Scan CMOS |
| | Minimum Illumination | 0.3~0.5Lux (Color mode) ,0Lux (B&W mode) |
| | Lens | 4.0mm@F2.1 |
| | View Angle | 71.1° (diagonal) |
| | Night vision | Dual Filter,IR-Cut, 12 pcs 850nm Φ5mm IR LED IR irradiation distance:5~10m |
| Video | Encode format | H.264 main profile@level:4.0/Motion-JPEG/JPEG |
| | Three Stream | Main Stream: 720p (1280×720) @25fps Sub Stream: 360p(640×360)@25fps Third Stream: 180p(320×180)@10fps |
| | Bit Rate | 128~4096kbps |
| | Maximum frame rate | 25fps |
| | Image adjustment | Contrast、Brightness、 Saturation、 Hue |
| Audio | Input | Built-in -48 dB microphone |
| | Output | Built-in speaker(8Ω1W) |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Ethernet | 10Base-T / 100Base-TX, RJ45 connector |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc |
| | Wireless LAN | IEEE802.11b/g/n |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan-tilt | Pan-tilt | Pan: 355°, tilt: 120° |
| | Preset position | PC APP: support 16 positions, Phone APP:support 5 positions |
| Memory | Socket | TF Push-push socket,Maximum support 128GB; Cloud Storage |
| Alarm | Alarm Trigger | Motion detection |
| Physical Environmental | Rated voltage | DC 5V±5% |
| | Power consumption | Related power: 3.5W(IR LED on), Maximum power: 7W (Pan&Tilt on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Gross: 688 g(Note: in kind prevail) |
| | Package size | 208*154*137mm mm(L×W×H) |