



Specifications Model: C37S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W mode)
	Lens	4.0mm@F2.0
	View Angle	107° (diagonal)
	Night vision	Dual Filter,IR-Cut, 10pcs 850nm Φ 5mm IR LED, IR irradiation distance: 5~10m
Video	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream:1080p(1280X720)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8 Ω 1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 355°, tilt: 120°
	Preset position	PC APP: support 16 positions, phone: APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC 5V \pm 5%
	Power consumption	Related power: 2.20W(IR LED on), Maximum power: 4.85W(Pan-tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: 245(Note: in kind prevail)
	Package size	197*157*120mm (L×W×H)