



Specifications Model: C46

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/4 inch 720P Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W mode)
	Lens	3.2mm@F2.2
	View Angle	85° (diagonal)
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm Φ 5mm IR LED, IR irradiation distance:5~10m
Video	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:720p(1280X720)@25fps Sub Stream:360p(640X360)@25fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	25fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8 Ω 1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 350°,tilt: 90° (Privacy position is not included)
	Preset position	PC APP: support 16 positions, phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC 5V \pm 5%
	Power consumption	Related power:2.4W(IR LED on), Maximum:5.25W(Pan&Tilt on)
	Operating condition	Temperature:-10~50 $^{\circ}$ C ,humidity:<90%
	Weight	Gross: 210g(Note: in kind prevail)
	Package size	192x153x112mm(L \times W \times H)