



Specifications Model: C92S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux(color mode),0Lux(B&W mode)
	Lens	4mm@F2.1
	View Angle	107.7°Diagonal
	Nightvision	Dual Filter,IR-Cut, 6pcs 850nm SMD IR LED, IR irradiation distance:5~10m
Video	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
Audio	Input	Built-in -48dB Microphone
	Output	Built-in 8Ω1W speaker
	Sampling frequency	8KHz
	Sampling Bit wide	16bit
	Encode format/Bit rate	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC5V±5%
	Power consumption	Typical:3.5W(IR LED turn on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: TBDg(Note: in kind prevail)
	Package size	148*126*90mm(L×W×H)