



Specifications Model: C93S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.7Lux (Color mode) ,0.3Lux (B&W mode)
	Lens	4.0mm@F2.1
	View Angle	107° (diagonal)
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm SMD IR LED IR irradiation distance:5~10m
Video	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream: 1080p (1920×1080) @15fps Sub Stream: 360p(640×360)@15fps Third Stream: 180p(320×180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
Audio	Input	Built-in -48 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	N/A
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP, RTSP, P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	N/A	/
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power:2W(IR LED on)
	Operating condition	Temperature:-10~50℃ ,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	TBD mm(L×W×H)