

C38S-P SPEC

| | | |
|-------------------------------|----------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/2.9inch 1080p Progressive Scan CMOS |
| | Minimum Illumination | 0.3~0.5Lux (Color mode) ,0Lux (B&W Mode) |
| | Lens | 4mm |
| | View Angle | 103° (diagonal) |
| | Night vision | Dual Filter,IR-Cut, 11pcs 850nm Plug-in IR LED IR irradiation distance:5~10m |
| Video | Encode format | H.264 main profile@level:4.0/Motion-JPEG/JPEG |
| | Three Stream | Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@15fps |
| | Bit Rate | 128~4096kbps |
| | Maximum frame rate | 15fps |
| | Image adjustment | Auto |
| Audio | Input | Built-in -38 dB microphone |
| | Output | Built-in speaker(8Ω1W) |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Ethernet | 10Base-T / 100Base-TX, RJ45 connector |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,ONVIF, NTP,RTSP,P2P etc |
| | Wireless LAN | IEEE802.11b/g/n |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan-tilt | Pan-tilt | Pan: 355°,Tilt: 120° |
| | Preset position | PC APP: support 16 positions, phone APP:support 5 positions |
| Memory | Socket | TF Push-push socket,Maximum support 128GB |
| Alarm | Alarm Trigger | Motion detection |
| Laser | Distance | 5~8 meters |
| Physical Environmental | Rated voltage | DC 5V±5% |
| | Power consumption | Related power:2.05W(IR LED on), Maximum Power: 4.55W (All function on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Gross: TBD g(Note: in kind prevail) |
| | Package size | 208 x 154 x 137 mm(L×W×H) |