



Specifications Model: C13S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.5Lux(color mode), 0.1Lux(B&W mode)
	Lens	3.6mm@F2.5
	View Angle	85°(Diagonal)
	Nightvision	Dual Filter,IR-Cut, 4pcs 850nm SMD IR LED, IR irradiation distance:10~15m
Video	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、 Saturation、 Hue
	Input	/
Audio	Output	Built-in Siren, Max 95 dB
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC12V±5%
	Power consumption	Related power:1.44W(IR not on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	245*107*80mm(L×W×H)
Others		Built-in RTC Chip, internet-free video recording and viewing