



Specifications Model: C37S

System	Operation system	Embedded Linux
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux (Color mode) ,0Lux (B&W Mode)
	Lens	4.0mm@F2.1
	View Angle	101° (diagonal)
	Night vision	Dual Filter,IR-Cut, 6pcs 850nm SMD IR LED IR irradiation distance:5~10m
Video	Encode format	H.265 coding. Compatible with.H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream:1080p(1920X1080)@30fps Sub Stream:360p(640X360)@30fps
	Bit Rate	128~4096kbps
	Maximum frame rate	30fps
	Image adjustment	Automatic
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan/Tilt	Preset position	PC APP: support 16 positions, phone APP:support 5 positions
Memory	Socket	Support T-Flash card (MAX.256GB); Cloud storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power:2.7W(IR LED on), Maximum Power: 4.3W (Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: 240 g(Note: in kind prevail)
	Package size	197x157x120mm(L×W×H)