

C19S SPEC

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.7Lux (Color mode) ,0.3Lux (B&W Mode)
	Lens	4.0mm@F2.5
	View Angle	101.5° (diagonal)
	Night vision	Dual Filter,IR-Cut, 2 pcs 850nm patch IR LED; 2 LED white lights,full colored night vision IR irradiation distance:5~15m
Video	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(640X360)@15fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Auto
Audio	Input	Waterproof microphone -38db
	Output	Built-in speaker(8Ω1W) Built-in 60 DB siren.
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Storage	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection, Siren and flash light alarm
Physical Environmental	Rated voltage	DC12V
	Power consumption	Related power:1.30W; Max power:2.50W
	Operating condition	Temperature:-10~50°C,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	TBD mm (L×W×H)