



## Specifications Model: C35S

<b>System</b>	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
<b>Image Capture</b>	Image sensor	HI3516E V200 1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	03.-0.5Lux(color mode), 0Lux(B&W mode)
	Lens	4.0mm@F2.0
	View Angle	101° (Diagonal)
	Night vision	Dual Filter,IR-Cut, 12pcs 850nm SMD IR LEDs, IR irradiation distance :5-10 meters
<b>Video</b>	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Resolution	2304x1296\1920x1080\640x480\320x240
	Bit Rate	128~4096kbps
	Frame rate	1-30fps
	Display frequency	60Hz、50Hz
	Image adjustment	Auto
<b>Audio</b>	Input	Built-in -38dB microphone
	Output	8 ohm 1W
	Sampling frequency/Bit width	8KHz/16bit
	Compression standard/Bit rate	ADPCM/32kbps
<b>Network</b>	Ethernet	RJ-45(10 / 100Base-T)
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Pan &amp;Tilt</b>	Rotating angel	Horizontal 355° vertical 120°
	Preset position	Support 16 preset positions (only support 5 on phone app. )
<b>Memory</b>	Socket	Cloud Storage / TF card (maximum support 256G)
<b>Alarm</b>	Alarm Trigger	Motion detection
<b>Physical Environmental</b>	Rated voltage	DC5V±5%
	Power consumption	Rated power:3.2W(IR lights are on) Maximum power:4.15W(Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Gross weight	637g ( in kind prevail)
	Net weight	334g ( in kind prevail)
	Product size	208*154*137 mm (L x W x H)
	Package size	124X115X137mm (L x W x H)