

Specifications Model: CS22S

| | | |
|-------------------------------|----------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | HI3518E V300 & 1/2.9 inch 1080p Progressive Scan CMOS |
| | Minimum Illumination | 0.5Lux (Color mode) ,0.1Lux (B&W Mode) |
| | Lens | 4.0mm@F2.0 |
| | View Angle | 101° (diagonal) |
| | Night vision | Dual Filter,IR-Cut, 6pcs 850nm SMD IR LED IR irradiation distance:5~10m |
| Video | Encode format | H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG |
| | Resolution | 2304x1296\1920x1080\640x480\320x240 |
| | Bit Rate/FPS/Frequency | 128~4096kbps/1~30pfs/60Hz、50Hz |
| | Image adjustment | Auto |
| Audio | Input | Built-in -38 dB microphone |
| | Output | Built-in speaker(8Ω1W) |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Wireless LAN | IEEE802.11b/g/n |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan-tilt | Pan-tilt | Pan: 334°,Tilt: 110° |
| | Preset position | PC APP: support 16 positions, phone APP:support 5 positions |
| Memory | Socket | TF Push-push socket,Maximum support 256GB |
| Alarm | Alarm Trigger | Motion detection, Humanoid detection, Humanoid tracking, Cry detection, Smoke siren alarm, Off-duty monitoring, Electronic fence |
| Physical Environmental | Rated voltage | DC 5V±5% |
| | Power consumption | Related power:2.8W(IR LED on), Maximum Power: 4.3W (Pan&Tilt on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Gross: 185 g(Note: in kind prevail) |
| | Package size | 110x110x185 mm(L×W×H) |



Specifications Model: CS22S