

Specifications Model: C35S

System	Operation system	Embedded Linux OS	
	Online visitor	Support 4 visitors at the same time	
Image Capture	Image sensor	C35	1/4 inch 720p Progressive Scan CMOS
		C35S	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux (Color mode) ,0Lux (B&W mode)	
	Lens/View Angle	C35	4.0mm@F2.1/71.1° (Diagonal)
		C35S	4.0mm@F2.0/101° (Diagonal)
	Night vision	C35	Dual Filter,IR-Cut, 12 pcs 850nm Φ5mm IR LED IR irradiation distance:5~10m
C35S		Dual Filter,IR-Cut, 12 pcs 850nm patch IR LED IR irradiation distance:5~10m	
Video	Encode format	C35	H.264 main profile@level:4.0/Motion-JPEG/JPEG
		C35S	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Three Stream	C35	Main Stream: 720p(1280×720)@25fps Sub Stream: 360p(640×360)@25fps Third Stream: 180p(320×180)@10fps
		C35S	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Substream: 360p(640×360)@15fps
	Bit Rate	128~4096kbps	
	Maximum frame rate	C35	25fps
		C35S	30fps
	Image adjustment	Contrast、Brightness is adjustable	
Audio	Input	Built-in -38 dB microphone	
	Output	Built-in speaker(8Ω1W)	
	Sampling frequency / width	8KHz/16bit	
	Compression standard	ADPCM/32kbps	
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector	
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc	
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode	
	Wireless LAN Frequency	2.4~ 2.4835GHz	
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption	
Pan-tilt	Pan-tilt	Pan: 355°, tilt: 120°	
	Preset position	PC APP: support 16 positions, Phone APP:support 5 positions	
Memory	Socket	C35	TF Push-push socket,Maximum support 128GB; Cloud Storage
		C35S	TF Push-push socket,Maximum support 256GB; Cloud Storage;NVR;NAS
Alarm	Alarm Trigger	C35	Motion detection
		C35S	Support motion detection, humanoid detection, humanoid tracking, crying monitoring, smoke detector alarm detection,

Specifications Model: C35S

			absence monitoring, electronic fence	
Physical Environmental	Rated voltage	DC 5V±5%		
	Power consumption	C35	Related power: 3.5W(IR LED on), Maximum power: 7W (Pan&Tilt on)	
		C35S	Related power: 3.2W(IR LED on), Maximum power: 4.15W (Pan&Tilt on)	
	Operating condition	Temperature:-10~50℃,humidity:<90%		
	Weight	C35	Gross: 688g(Note: in kind prevail)	
		C35S	Net: 328g Gross: 615g(Note: in kind prevail)	
	Package size	208*154*137 mm(L×W×H)		