

Specifications Model: C63S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9 inch 1080p Progressive Scan CMOS sensor
	Minimum Illumination	0.3-0.5Lux(color mode), 0 Lux(B&W mode)
	Lens	2.3mm@F2.4
	View Angle	180°(Horizontal)
	Night vision	Automatic switching of dual filters, 3pcs 850nm patch infrared lamps, IR irradiation distance:5-10m
Video	Encode format	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Streams	Main stream: 1920*1080@30fps Substream: 640*360@ 25fps/30fps
	Bit Rate/Max Fps	128~4096kbps/30pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -38±5dB microphone
	Output	8 Ω 1W speaker
	Sampling frequency /Bit width	8KHz/16bit
	Compression standard /code rate	ADPCM/32kbps
Network	Ethernet	10Mbps/100Mbps adaptive /RJ45 interface
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB
Alarm	Alarm Trigger	Motion detection, human detection, crying detection, smoke alarm detection, absence monitoring
Physical Environmental	Rated voltage	DC12V±5%@DC
	Power consumption	Rated power: 5.16W (with infrared lights on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: 365.5g Gross: 584.5g(Note: in kind prevail)
	Package size	240x126x97mm (L×W×H)