

Specifications Model: C97

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/4 inch 720p Progressive Scan CMOS
	Minimum Illumination	0.1~0.5Lux (Color mode) ,0Lux (B&W Mode)
	Lens	3.2mm@F2.2
	View Angle	88° (diagonal)
	Night vision	Dual filter automatically switch, 6pcs 850nm patch infrared lamps. IR irradiation distance:5~10m
Video	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Streams	Main stream 1280*720@30fps Sub stream 640*360@30fps
	Bit Rate/max FPS/Frequency	128~4096kbps/15pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -38 dB microphone
	Output	Built-in 8Ω1W speakers
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB
Alarm	Alarm Trigger	Motion detection, Human detection, Crying detection, Smoke alarm detection, Absence monitoring
Physical Environmental	Rated voltage	DC5V±5%@Micro USB
	Power consumption	Related power: 3.5W(IR LED on)/ Max power: 3.3W
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: TBD Gross: TBD g(Note: in kind prevail)
	Package size	TBD mm(L×W×H)