

Specifications Model: c41

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/4 inch 720p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux (Color mode) ,0 Lux (B&W mode)
	Lens/View Angle	3.6mm@F2.0/85° (diagonal)
	Night vision	Dual filters automatically switch. 6pcs 850nm patch IR LEDs IR radiating distance:5~10m
Video	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Streams	Main stream: 720p(1080×720)@25/30fps/1080P (1920*1080) @25fps Sub stream: 360p(640×360)@15fps
	Bit rate/Fps	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 345°,tilt: 84°
	Preset position	PC APP: support 16 positions, phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 256GB; Cloud Storage
Alarm	Alarm Trigger	Support motion detection, human detection,crying monitoring, smoke alarm detection, absence monitoring
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power:2.7W(IR LED on), Maximum power:3.5W(Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: TBD g Gross: TBD g (Note: in kind prevail)
	Package size	TBD mm (L×W×H)