



Specifications Model: CS52Q

| | | |
|-------------------------------|----------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/3 inch Progressive Scan CMOS |
| | Minimum Illumination | 0.3~0.5Lux (Color mode) ,0Lux (B&W Mode) |
| | Lens | 4.0mm |
| | View Angle | 101° (Diagonal) |
| | Night vision | Automatic switching of dual filters, 2pcs 850nm infrared lamps and 2 high-power white lamps, with irradiation distance of 15-20 meters |
| Video | Encode format | H.264+/H.264 main profile/Motion-JPEG/JPEG |
| | Streams | 2560×1440\640*360\640*360 |
| | Bit Rate/Max Fps | 128~4096kbps/30fps |
| | Image adjustment | Brightness and contrast can be adjusted |
| Audio | Input | Built in -28±5db microphone |
| | Output | Built-in 8Ω2w speakers |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Ethernet | 10Mbps/100Mbps adaptive /RJ45 interface |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P 等 |
| | Wireless LAN | IEEE802.11b/g/n, Supports AP mode |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Memory | Socket | TF Push-push socket,Maximum support 256GB; Cloud Storage |
| Alarm | Alarm Trigger | Support motion detection, human detection, crying monitoring, smoke alarm detection, absence monitoring |
| Physical Environmental | Rated voltage | DC12V±5% |
| | Power consumption | Rated power: 3.91W Related power:5.52W(IR on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Net: TBD g Gross: TBD g(Note: in kind prevail) |
| | Package size | TBD mm(L*W*H) |