

Specifications Model: C59S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	Lens	4.0mm@F2.1
	View Angle	101° (diagonal)
	Night vision	Dual Filter,IR-Cut, 4pcs 850nm IR LED, 4pcs spotlight and 1 blue and red alarm light IR irradiation distance:15m
Video	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Resolution	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Sub stream: 360p(640×360)@15fps
	Bit Rate/FPS	128~4096kbps/1~30pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -28±3 dB microphone
	Output	Built-in 8Ω2W speakers
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~2.4835GHz; 5.725~5.850GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB,Cloud storage,NVR,NAS
Alarm	Alarm Trigger	Motion detection, Human detection, Smoke alarm detection, Absence monitoring
Physical Environmental	Rated voltage	DC 12V±5%
	Power consumption	Related power: 6W(IR LED on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: TBD Gross: TBD g(Note: in kind prevail)
	Package size	TBD mm(L×W×H)