


| CS64Q | | | |
|---|---------------------|---|---|
| Product image | | Features | |
|  | | ★ 4K 8MP | |
| | | ★ Black and white night vision, color night vision | |
| | | ★ ISP image processing technology, preserving true colors | |
| | | ★ Human detection, real time alerts | |
| No. | Sorts | Type | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | Ingenic T41NQ |
| | | Memory | 512Mb |
| | | Lens | 4mm F2.0 |
| | | Image sensor | 1/2.7 4MP progressive scanning CMOS sensor |
| | | Min. Illumination | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | | Night vision | Black and white night vision, full-color night vision |
| | | Viewing angle | Diagonal angle: 109 ° |
| 3 | Video | Resolution | 4K 3840x2160/15FPS 8MP |
| | | Night vision | 20-50 meters |
| | | Compression | H.264 main profile/Motion-JPEG/JPEG |
| | | IR control | IR-CUT, soft photosensitive control |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| 4 | Audio | Input | Built-in -38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| | | Sampling | 8KHz/16bit |
| | | Compression | G711A |
| 5 | Pan/Tilt | Rotation angle | Pan: 265° tilt: 95° |
| 6 | Network | Network interface | 10Mbps/100Mbps |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
| | | Wireless frequency | 2.4G |
| | | Wireless security | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| 7 | Storage | External TF card | Supports T-Flash cards (up to 256GB) |
| | | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| 8 | Alarm | Alarm detection | Motion detection, human detection, human framing, human tracking, siren alarm, and area detection |
| 9 | Physical Indicators | Rated voltage | DC12V±5% |
| | | Power consumption | Power: 4.3W; Maximum power: 13.8W |
| | | Operating condition | Working temperature: -10 ~ 55°C, working humidity <90% |
| | | Weight | Net weight: 426g; Gross weight: 680g |
| | | Camera size | 171x112x179mm |
| | | Packaging box size | 195x205x130mm |
| | | Carton size | 545x425x415mm,16PCS/Carton |