

Specifications Model: CS64

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.1 Lux (B&W mode) ,0.5Lux (Color mode)
	Lens	3.6mm@F2.0
	View Angle	97.2° (diagonal)
	Night vision	Dual filters automatically switch. 8pcs 850nm high power patch IR LEDs IR radiating distance:15~20m
Video	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Resolution	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Sub stream: 360p(640×360)@15fps
	Bit rate/Fps/Display frequency	128~4096kbps/1~30pfs/60Hz、50Hz
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -38±3dB microphone
	Output	Built-in speaker(8Ω2W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 355°,tilt: 95°
	Preset position	PC APP: support 16 positions, phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 256GB; Cloud Storage;NVR;NAS
Alarm	Alarm Trigger	Support motion detection, human detection, human tracking, smoke alarm detection, absence detection
Physical Environmental	Rated voltage	DC 12V±5%
	Power consumption	Related power:3.5W (IR on)/maximum power: 11W
	Operating condition	Temperature:-10~50℃ ,humidity:<90%
	Weight	Net: 460g(Note: in kind prevail)
	Package size	205×195×130mm (L×W×H)