

Specifications Model: CS65-X5

| | | |
|-------------------------------|----------------------------|---|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/2.9 inch Progressive Scan CMOS |
| | Minimum Illumination | 0.5Lux (Color mode) ,0.1Lux (B&W Mode) |
| | Lens/View angle | 3.5-9.5mm zoom lens/ 41 ~ 110° (Diagonal) |
| | Night vision | Automatic switching of dual filters, 6pcs 850nm infrared lights and 4pcs high-power spotlights, with irradiation distance of 15-20 meters |
| Video | Encode format | H.264+/H.264 main profile/Motion-JPEG/JPEG |
| | Streams | Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps |
| | Bit Rate/Max Fps | 128~4096kbps/30fps |
| | Image adjustment | Brightness and contrast can be adjusted |
| Audio | Input | Built in -28db±5dB microphone |
| | Output | Built-in 8Ω2w speakers |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Ethernet | 10Mbps/100Mbps adaptive /RJ45 interface |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P 等 |
| | Wireless LAN | IEEE802.11b/g/n, Supports AP mode |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan/Tilt | Pan-tilt | Pan: 355°,tilt: 95° |
| | Preset position | PC Client: support 16 positions, Mobile APP:support 5 positions |
| Memory | Socket | TF Push-push socket,Maximum support 256GB; Cloud Storage;NVR: NAS |
| Alarm | Alarm Trigger | Support motion detection, human detection, human tracking,smoke alarm detection, absence detection |
| Physical Environmental | Rated voltage | DC12V 2A ±5% |
| | Power consumption | Rated power: 3.9W (IR on)/ Max power: 12.3W |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Net: 915g Gross: TBD g(Note: in kind prevail) |
| | Package size | 205x195x130mm(L*W*H) |