

Specifications Model: C38S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum illumination	0.3~0.5 Lux (Color mode) , 0Lux (B&W mode)
	Lens/Viewing Angle	4.0mm@F2.0/101° (diagonal)
	Night vision	Dual Filter, IR-Cut, 12 pcs 850nm IR LED, IR irradiation distance:10m
Video	Encode format	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Resolution	Main Stream:1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Sub Stream:360p(640×360)@15fps
	Bit Rate/Fps	128~4096kbps/30fps
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, RTSP, P2P etc.
	Wireless LAN	IEEE802.11b/g/n; Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 355°, tilt: 120°
	Preset position	PC App: Supports 16 positions; phone App: Supports 5 positions
Memory	Socket	TF Push-push socket, Maximum support 256GB; Cloud Storage: NVR; NAS
Alarm	Alarm Trigger	Motion detection; Humanoid detection; Humanoid tracking; Sound detection; Smoke detector alarm detection; Absence monitoring; Electronic fence
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power: 3.2W(IR LED on), Maximum power: 4.15W(Pan-tilt on)
	Operating condition	Temperature: -10~50℃, humidity:<90%
	Weight	Net: 325g Gross: 620g(Note: in kind prevail)
	Package size	208*154*137mm (L×W×H)