


CS24

Product Image		Features	
		★F2.0 large aperture, more light inputs, clearer night vision	
		★ISP image processing technology, preserving true colors	
		★Stable Wi-Fi connectivity, always online	
		★Supports remote monitoring via mobile & PC clients anytime, anywhere	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Tsingmicro TX5110CV206
		Memory	512Mb
		Lens	3.6mm
		Image sensor	1/3.3" GC20C3 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (Color), 0.1Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Infrared Night Vision
3	Video	Field of View	79°
		Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP (Interpolation)
		Night vision	5-10m
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Vertical flip & OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency / Bit depth	8KHz/16bit
		Compression standard/Bit rate	G711A
5	PTZ	Movement range	Pan: 345° Tilt: 84°
6	Network	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK Data encryption
7	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing,human tracking, and area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.6W (0.32A) Maximum power: 2.25W (0.45A)
		Operating condition	Temperature: -10 ~ 45°C; Humidity: < 90%
		Weight	Net weight: 240g, Gross weight: 520g
		Product Dimension	127x103x132mm
		Package Dimension	197x157x120mm
		Carton Dimension	620x415x340xmm
		QTY/CTN	20PCS
		Package Contents	Camera x1, mount x1, power adapter x1, power cable x1, user manual x1, screw pack x1