

Sorts	Type	Parameters
<b>System</b>	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/3 inch 1440p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux (Color mode) , 0.1 Lux (B&W mode)
	Lens/Viewing angle	4mm@F2.3/101°(Diagonal)
	Night vision	IR-CUT with auto-switching, 9 pcs LED lights, 6 pcs IR LED lights; Irradiation distance: 20~30 m
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1440p(2560×1440) @30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
<b>Audio</b>	Input	Built-in -38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
<b>Network</b>	Network interface	10Mbps/100Mbps adaptive /RJ45
	Network protocol	TCP/IP,HTTP,TCP,ONVIF,UDP,DHCP,DNS,NTP,RTSP, P2P etc.
	Wireless network	IEEE802.11b/g/n; Supports AP mode
	Wireless frequency	2.4GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Pan &amp; Tilt</b>	Pan & Tilt	Pan 268° /Tilt 110°
	Preset position	Supports 16 (Mobile phone App only supports 5) preset positions
<b>Storage</b>	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS
<b>Alarm</b>	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid tracking; Smoke alarm; Absence detection alarm; Alarm voice prompt , flash & irradiation; LED light Timing ON &

**Shenzhen VStarcam Technology Co., Ltd**



My safety, My rule!

## Model: CS668Q

		OFF
<b>Physical Indicators</b>	Rated voltage	DC12V±5%
	Power consumption	Rated power: 4.5W (with IR LED ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: -10~50°C, Humidity: <90%
	Weight	(Note: in kind prevail)
	Size	(230x205x140) mm

**Shenzhen VStarcam Technology Co., Ltd**

[www.vstarcam.com](http://www.vstarcam.com)