

	<b>Selling points</b>	<ol style="list-style-type: none"> <li>1. Wireless &amp; wired connection, 3MP, 4 inch (Dual antenna)</li> <li>2. Red and blue alarm lights</li> <li>3. Dual light sources; Night vision: 30 m; 9 pcs LED lights, 6 pcs IR LED lights</li> <li>4. Two-way talk; Pendant-mounted available; Rainproof &amp; dustproof</li> <li>5. Storage card recording supports up to 256G</li> <li>6. Delimitation detection; Humanoid framing; Humanoid tracking; Humanoid detection alarm</li> <li>7. LED light timing ON &amp; OFF</li> <li>8. Alarm voice prompt, flash &amp; irradiation; Smoke alarm; Absence detection alarm</li> </ol>
<b>Sorts</b>	<b>Type</b>	<b>Parameters</b>
<b>System</b>	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux (Color mode) , 0.1 Lux (B&W mode)
	Lens/Viewing angle	3.6mm@F2.0/110°(Diagonal)
	Night vision	IR-CUT with auto-switching, 9 pcs LED lights, 6 pcs IR LED lights; Irradiation distance: 20~30 m
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
<b>Audio</b>	Input	Built-in -38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
<b>Network</b>	Network interface	10Mbps/100Mbps adaptive /RJ45
	Network protocol	TCP/IP, HTTP, TCP, UDP, DHCP, ONVIF,DNS, NTP, RTSP, P2P etc.
	Wireless network	IEEE802.11b/g/n; Supports AP mode
	Wireless frequency	2.4GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Pan &amp; Tilt</b>	Rotation angle	Pan 355° /Tilt 110°
	Preset position	Supports 16 (Mobile phone App only supports 5) preset

		positions
<b>Storage</b>	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS
<b>Alarm</b>	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid tracking; Smoke alarm; Absence detection alarm; Alarm voice prompt , flash & irradiation; LED light timing ON & OFF
<b>Physical indicators</b>	Rated voltage	DC12V±5%
	Power consumption	Rated power: 4.5W (with IR LED ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: -10~50℃, Humidity: <90%
	Weight	Net: 578g (Note: in kind prevail)
	Size	(230x205x140) mm