



My safety, My rule!

Model: CS881Q-X5

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	Image sensor	1/3 inch progressive scan CMOS sensor
	Minimum illumination	0.5 Lux (Color mode), 0.1 Lux (B&W mode)
	Lens/Viewing angle	3.5-9.5mm Zoom lens/Diagonal Viewing angle: 99.3°~40.5°
	Night vision	IR-CUT with auto-switching, 18 850nm patch IR LED lights, Irradiation distance: 20-30 m
Video	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1520P (2688*1520) @15fps/1440p(2560×1440)@25fps Substream: 360p(640×360)@15fps
	Bit rate	128~4096kbps
	Maximum frame rate	30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8Ω1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P, ONVIF etc.
	Wireless network	IEEE802.11b/g/n
	Wireless frequency	2.4GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage
Alarm	Alarm detection	Supports Motion detection; Humanoid detection; Smoke sound detection; Absence detection; Delimitation detection
Physical Indicators	Rated voltage	DC12V 2A ±5%, Support POE
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	Net: 530g (Note: in kind prevail)

Shenzhen VStarcam Technology Co., Ltd

www.vstarcam.com