| BG54              |                     |                                    |  |
|-------------------|---------------------|------------------------------------|--|
| Product Picture   |                     | duct Picture                       | Features   |
|                   |                     |                                    | ★4G connection   |
|                   |                     |                                    | ★ Remote active wake-up, two-way voice intercom  |
|                   |                     |                                    | ★ Quick start, start recording within 400ms  |
|                   |                     |                                    | · · · · · · · · · · · · · · · · · · ·  |
|                   |                     |                                    | ★ Intelligent detection of human movement, intelligent alarm push  |
|                   |                     |                                    | ★ 5200mAh battery power supply, low power warning  |
|                   |                     |                                    | ★Support AOV mode (Chinese version only)   |
|                   |                     |                                    | ★ Ultra low power system optimization  |
|                   |                     |                                    | ★Free cloud storage alarm videos   |
|                   |                     |                                    | ★Support external solar panels to continuously power the camera.   |
| No. Category Type |                     | Туре                               | Parameter  |
| 1                 | System              | Operating system                   | Embedded Linux   |
|                   |                     | Online visitor                     | Supports 4 visitors at the same time   |
|                   |                     | APP                                | O-KAM Pro  |
|                   | Collection          | CPU                                | T23  |
| 2                 |                     | Image sensor                       | OV 02N10   |
|                   |                     | Lens                               | Focal length 4mm   |
|                   |                     | Viewing angle                      | Diagonal 110°  |
| 3                 | Video               | Night vision                       | Black and white night vision/full color night vision, 6pcs 850nm infrared lights, 2pcs white light lights  |
|                   |                     | Compression standard               | H.264 /JPEG  |
|                   |                     | Pixels                             | 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs   |
|                   |                     |                                    | HD 2304x1296@15fps 512kpbs   |
|                   |                     |                                    | SD 640x360@15fps 256kpbs   |
|                   |                     | Image adjustment                   | 180° rotation  |
|                   |                     | Input                              | Built-in — 38dB microphone   |
| 4                 | Audio               | Output                             | Built-in 8Ω1W speaker  |
|                   |                     | Sampling frequency/bit width       | 8KHz/16bit   |
|                   |                     | Compression standard / Bit rate    | G711A  |
|                   | AI                  | Human detection                    | Human detection, filtering invalid video contents  |
|                   |                     | Area detection                     | Free daub, only monitoring the areas concerned by users  |
| 5                 |                     | Smart notification sound           | Different devices push different sounds, so that you can know exactly which device is triggered(Not supported by some mobile phones, such as Huawei)   |
|                   |                     | Intelligent alarm sound            | Set different equipment alarm sounds according to different scenarios  |
|                   |                     | More Al functions (testing)        | Pets, vehicles, parcels, etc   |
| 6                 | Network             | Networking                         | Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add;  |
|                   |                     | Chinese version                    | FDD:B1/B3/B5/B8  |
|                   |                     | Chinese version                    | TDD:B34/B38/B39/B40/B41  |
|                   |                     | American version                   | FDD: B2/4/5/12/13/25/26  |
|                   |                     | European version                   | FDD: B1/B3/B7/B8/B20/B28   |
| 7                 | Key                 | On/Off                             | Turn on/off  |
| $\perp$           | 1                   | Reset key                          | Long press to restore factory settings   |
| 8                 | Storage             | External TF card                   | Support TF card (up to 256GB)  |
|                   |                     | Cloud storage                      | Free loop cloud storage Support PIR human detection  |
| 9                 | Alarm               | Alarm detection  Power saving mode | PIR triggered recording  |
| 10                | Working Mode        | AOV mode                           |  |
|                   |                     | Smart sleep mode                   | 24-hour full-time recording, when human figure is recognized or PIR triggered recording  24-hour full-time recording (when battery level is above 40%) |
|                   |                     | Super power saving mode            | PIR triggered recording, camera cannot be woken up through App   |
| 11                | Physical Indicators | Charging voltage                   | 5V/2A TYPE-C   |
|                   |                     | Power supply                       | 5200mAh battery  |
|                   |                     | Consumption                        | Sleep standby current 5mA, working current: 400-600mA  |
|                   |                     | Operating condition                | Temperature: -10 ~ 55°C; Humidity: < 90%   |
|                   |                     | Weight                             | Net weight: 200g Gross weight: 363g  |
|                   |                     | Size                               | Camera: 89.5*56.5*59.5mm Pacakging box: 152*119*79mm   |
|                   |                     | Packing list                       | Camera*1, bracket*1, charging cable*1, manual*1  |