

Specifications Model: CS52Q

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/3 inch Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux (Color mode) ,0Lux (B&W Mode)
	Lens	4.0mm
	View Angle	101° (Diagonal)
	Night vision	Automatic switching of dual filters, 2pcs 850nm infrared lamps and 2 high-power LED lights, with irradiation distance of 15-20 meters
Video	Encode format	H.264+/H.264 main profile/Motion-JPEG/JPEG
	Streams	2560×1440\640*360\640*360
	Bit Rate/Max pfs	128~4096kbps/30pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built in -28±5dB microphone
	Output	Built-in 8Ω2W speakers
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Mbps/100Mbps adaptive /RJ45 interface
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4GHz/5GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB; Cloud Storage
Alarm	Alarm Trigger	Support Motion detection, Humanoid detection, Crying detection, Smoke sound detection, Absence detection
Physical Environmental	Rated voltage	DC12V±5%
	Power consumption	Rated power: 3.91W Related power:5.52W(IR on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	(Note: in kind prevail)
	Package size	(Note: in kind prevail)