


CS665Q			
Product Image		Features	
		★4MP Ultra HD	
		★Black and white night vision, full color night vision	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts, red and blue light warning	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenuic T41LQ
		Memory	512Mb
		Lens	4mm F2.0
		Image sensor	1/3 4MP progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
3	Video	Viewing angle	Diagonal: 109°
		Resolution	4MP 2560x1920/15FPS
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
5	Pan/Tilt	Compression standard/Bit Rate	G711A
		Rotation angle	Pan: 350° tilt: 90°
6	Network	Network interface	10Mbps/100Mbps, adaptive/RJ45 interface
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless frequency	2.4G-5.8G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, siren alarm and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 4.56W (0.38A); Maximum power: 14.52W (1.21A)
		Operating condition	Working temperature: -10 ~ 55°C, working humidity <90%
		Weight	Net weight: 453g; Gross weight: 853g
		Camera size	165x112x143mm
		Packaging box size	195x205x130mm
		Carton size	545x425x415mm, 16PCS/CARTON