



My safety, My rule!

Model: CG630Q-X30

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	Image sensor	1/3 inch progressive scan CMOS sensor
	Minimum illumination	0.1 Lux (B&W mode) , 0.5 Lux (Color mode)
	Lens/Viewing angle	4.7-141mm zoom lens/Diagonal: 64.2°@1X, 3.9°@30X
	Night vision	IR-CUT with auto-switching, 6PCS 850nm IR LED lights+3PCS laser lights; Irradiation distance: 100~200 m
Video	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Multi-stream	Main stream:1520P (2688*1520) @25fps Substream:360p(640*360)@25fps
	Bit rate	128~4096kbps
	Maximum frame rate	25fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -28dB microphone
	Output	Built-in 8Ω 2 W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	4G(China) LTE	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	4G(EU) LTE	WCDMA: B1/B5/B8 FDD: B1/B3/B5/B7/B8/B20 TDD:B38/B40/B41
Pan & Tilt	Pan & Tilt	Pan 350°/Tilt 98°
	Preset position	Supports 16(Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud storage; NVR; NAS
Alarm	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid framing; Smoke sound detection; Absence detection; Delimitation detection
Physical Indicators	Rated voltage	DC12V 3A
	Power consumption	Rated power: 12.6 W(with IR LED lights ON)/Max power: 21 W
	Operating condition	Temperature: -10~50℃; Humidity: <90%
	Weight	Net weight: 2380g Gross weight: 3450g (Note: in kind prevail)
	Size	420x320x235mm (LxWxH)

Shenzhen VStarcam Technology Co., Ltd

www.vstarcam.com