


CS49L

Product Image		Features	
		★F2.0 large aperture, more light inputs, clearer night vision	
		★Dual-core light board, full color day and night	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic T23N
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.27" 1080p progressive scanning CMOS sensor
		Minimum	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night vision	Black and white night vision, full-color night vision
3	Video	Viewing angle	Diagonal: 82°
		Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP(Interpolation)
		Night vision	5-10meter
		Compression	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
5	Pan&Tilt	Compression	G711A
		Angle	Pan: 325° Tilt: 55°
		Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
6	Network	Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK
		External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
7	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection,human tracking
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.75W (0.35A); Maximum power: 3.25W (0.65A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
		Weight	Net weight: 190g Gross weight: 420g
		Camera size	170x150x108mm
		Packaging box size	90x90x185mm
		Carton size	470x470x395mm,50PCS/carton