

Specifications Model: C24S

| | | |
|-------------------------------|-----------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | CPU/Image sensor | 1/2.7 inch 1080p Progressive Scan CMOS |
| | Minimum illumination | 0.5Lux (Color mode) ,0Lux (B&W Mode) |
| | Lens/Viewing Angle | 4.0mm@F2.0/84° (diagonal) |
| | Night vision | Dual Filter,IR-Cut, 6pcs 850nm patch IR LED; IR irradiation distance:5~10m |
| Video | Encode format | H.264 main profile/Motion-JPEG/JPEG |
| | Resolution | Main Stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Substream: 360p(640×360)@15fps |
| | Bit Rate/Maximum frame rate | 128~4096kbps/30fps |
| | Image adjustment | Brightness and contrast can be adjusted |
| Audio | Input | Built-in -38 dB microphone |
| | Output | Built-in speaker(8Ω1W) |
| | Sampling frequency / width | 8KHz/16bit |
| | Compression standard | ADPCM/32kbps |
| Network | Ethernet | 10Base-T / 100Base-TX, RJ45 connector |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc |
| | Wireless LAN | IEEE802.11b/g/n; Supports AP mode |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption |
| Pan-tilt | Pan-tilt | Pan: 345°,Tilt: 84° |
| | Preset position | Supports 16(Mobile phone App supports 5) preset positions |
| Memory | Memory function | Supports T-Flash card; Maximum support 256GB; Cloud storage: NVR; NAS |
| Alarm | Alarm Trigger | Motion detection; Humanoid detection; Humanoid tracking; Crying detection; |
| Physical Environmental | Rated voltage | DC 5V±5% |
| | Power consumption | Related power:2.5W(With IR LED on), Maximum Power: 5.6W (With Pan&Tilt on) |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Net: 245g Gross: 520g (Note: in kind prevail) |
| | Package size | 197*157*120 mm(L×W×H) |