



Specifications Model: C26/C26S

System	Operation system	Embedded Linux OS	
	Online visitor	Support 4 visitors at the same time	
Image Capture	CPU/Image sensor	C26	1/4 inch 720p Progressive Scan CMOS
		C26S	1/2.9 inch 1080p Progressive Scan CMOS
	Minimum Illumination	C26	0.3~0.5Lux (Color mode) ,0Lux (B&W Mode)
		C26S	0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	View Angle	C26	4.0mm@F2.1/91° (diagonal)
		C26S	4.0mm@F2.0/101° (diagonal)
Night vision	C26	Dual Filter,IR-Cut, 6pcs 850nm patch IR LED IR irradiation distance:5~10m	
	C26S	Dual Filter,IR-Cut, 2pcs 850nm patch IR LED IR irradiation distance:5~10m	
Video	Encode format	C26	H.264 main profile@level:4.0/Motion-JPEG/JPEG
		C26S	H.264 main profile/Motion-JPEG/JPEG
	Resolution	C26	Main Stream: 1280*720@25fps Sub stream: 640*360@25fps Third stream: 320*180@10fps
		C26S	Main Stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Sub stream: 360p(640×360)@15fps
	Bit Rate/FPS/Frequency	C26	128~4096kbps/25fps
		C26S	128~4096kbps/30fps
Image adjustment	Brightness and contrast can be adjusted		
Audio	Input	Built-in -38 dB microphone	
	Output	Built-in speaker(8Ω1W)	
	Sampling frequency / width	8KHz/16bit	
	Compression standard	ADPCM/32kbps	
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector	
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc	
	Wireless LAN	C26	IEEE802.11b/g/n
		C26S	IEEE802.11b/g/n ; Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz	
Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption		
Pan-tilt	Pan-tilt	Pan: 355°,Tilt: 110°	
	Preset position	PC APP: support 16 positions, phone APP:support 5 positions	
Memory	Socket	C26	TF Push-push socket,Maximum support 128GB; cloud storage
		C26S	TF Push-push socket,Maximum support 256GB; cloud storage
Alarm	Alarm Trigger	C26	Motion detection
		C26S	Motion detection, Humanoid detection, Humanoid tracking,



Specifications Model: C26/C26S

			Crying detection, Electronic fence
Physical Environmental	Rated voltage	DC 5V±5%	
	Power consumption	C26	Related power:2.55W(IR LED on), Maximum Power: 4.8W (Pan&Tilt on)
		C26S	Related power:2.8W(IR LED on), Maximum Power: 4.3W (Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%	
	Weight	Net: 185 g Gross: 450 g(Note: in kind prevail)	
	Package size	185*125*92 mm(L×W×H)	