



My safety, My rule!

## Model:C7824WIP

<b>System</b>	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
<b>Image Capture</b>	Image sensor	1/4 inch 720p Progressive Scan CMOS
	Minimum illumination	0.3~0.5Lux Color mode ,0 Lux B&W mode
	Lens	4.0mm@F2.0
	Viewing angle	85° diagonal
	Night vision	Dual Filter,IR-Cut 6pcs 850nm patch IR LED IR irradiation distance:5 10m
<b>Video</b>	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Resolution	720p(1280 720) 360p(640 360)
	Bit Rate/FPS/Frequency	128 4096kbps/1 30pfs/60Hz 50Hz
	Image adjustment	Brightness and contrast can be adjusted
<b>Audio</b>	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
<b>Network</b>	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
<b>Pan-tilt</b>	Pan-tilt	Pan 345°,tilt 84°
	Preset position	PC App support 16 positions, phone App:support 5 positions
<b>Memory</b>	Socket	TF Push-push socket,Maximum support 256GB; Cloud Storage;NVR;NAS
<b>Alarm</b>	Alarm Trigger	Motion detection; Humanoid detection; Humanoid tracking; Crying detection; Electronic fence
<b>Physical Environmental</b>	Rated voltage	DC 5V±5%
	Power consumption	Related power:2.5W(IR LED on), Maximum power:3.3W(Pan&Tilt on)
	Operating condition	Temperature:-10 50 ,humidity: 90%
	Weight	Net 250g(Note: in kind prevail)
	Package size	196*165*138mm (L×W×H)

Shenzhen VStarcam Technology Co., Ltd