

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	CPU/Image sensor	1/3 inch CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	4mm@F2.1/90.9°Diagonal
	Night Vision	IR-CUT with auto-switching, 6pcs 850nm IR LED light, 4pcs high power white lights, Irradiation distance 15~20 m
Video	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1296p(2304×1296)@25fps Substream: 360p(640×360)@25fps
	Bit rate/ maximum frame rate	128~4096kbps/25fps
	Image adjustment	Brightness, contrast are adjustable
Audio	Input	Built-in — 28dB microphone
	Output	Built-in 8Ω1.2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	4G(Domestic Version)Network	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	4G(Europe Version)Network	WCDMA: B1/B5/B8 FDD: B1/B3/B5/B7/B8/B20 TDD:B38/B40/B41
Pan & Tilt	Pan & Tilt	Pan 355°/Tilt 95°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Support T-Flashcard(max256GB); Cloud storage; NVR;NAS
Alarm	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid tracking; Delimitation detection
Physical Indicators	Rated voltage	DC12V±5%
	Power consumption	Rated power: 4 W(with IR LED lights ON)/ Max Power:12.4W
	Operating condition	Temperature: -10 ~ 50℃; Humidity: < 90%
	Weight	N.W.: 900g G.W.:1265g (Note: in kind prevail)
	Size	257x208x130mm (LxWxH)



我的安全，我做主

型号: CG65

深圳市威视达康科技有限公司

www.vstarcam.cn