


| | | |
|---------------------|-------------------------------|--|
| | CG663DR |  |
| Sorts | Type | Parameters |
| Collection | Operating system | Embedded Linux |
| | Online visitor | Supports 4 visitors at the same time |
| | CPU/Image sensor | Ingenic T40, 2 MP, dual lens, 1/3 inch 1440p progressive scan CMOS sensor |
| | Minimum illumination | 0.5 Lux(Color mode), 0.1 Lux(B&W mode) |
| | Lens | 4mm-6mm |
| | Night Vision | IR-CUT with auto-switching, Dual light source, irradiation distance 15-30 meters |
| | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | Data rate | Main stream:1080p(1920*1080)@25fps, Substream:360p(640*360)@15fps |
| | Bit rate/maximum frame rate | 128~4096kbps/25fps |
| | Image adjustment | Adjustable brightness and contrast |
| Audio | Input | Built-in - 38dB microphone |
| | Output | Built-in 8 Ω 1W speaker |
| | Sampling frequency/bit width | 8KHz/16bit |
| | Compression standard/Bit Rate | G.711/64kbps |
| Network | 4G band | WCDMA FDD TDD |
| Pan&Tilt | Rotation angle | Horizontal 350 °/Vertical 90 °,can be installed with 360 ° rotation |
| | Preset position | Supports 16 presets (mobile app only supports 5) |
| Storage | Storage functions | Supports T-Flash card(max supports 256GB); Cloud Storage;NVR;NAS |
| Alarm | Alarm detection | Support motion detection, humanoid detection, human tracking, alarm voice prompts, flash and illumination functions, and timed activation and shutdown of white light. |



我的安全，我做主

Model:CG663DR

| | | |
|---------------------|---------------------|---|
| Physical indicators | Rated voltage | DC12V |
| | Power consumption | Rated power: 4.5W (infrared light on)/maximum power: 11W (PTZ on) |
| | Operating condition | Temperature: -10~50°C; Humidity: <90% |
| | Weight | Note: in kind prevail |
| | Package size | Note: in kind prevail |