

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/3 inch progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	5.9mm~94.4mm zoom lens/Diagonal viewing angle 62°@1X~4° @18X
	Night vision	IR-CUT with auto-switching, 6PCS IR LED lights, Irradiation distance: 20~50 m
Video	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data Rate	Main stream:1520P (2688*1520) @25fps Substream:360p(640×360)@25fps
	Bit rate/maximum frame rate	128~4096kbps/25fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -28dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45
	Network Protocol	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, RTSP, P2P, etc.
	4G (China) LTE	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	4G (EU) LTE	FDD: B1/B3/B5/B7/B8/B20 TDD:B38/B40/B41 WCDMA: B1/B5/B8
Pan & Tilt	Pan & Tilt	Pan 350° /Tilt 100°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS
Alarm	Alarm detection	Motion detection; Humanoid detection; Humanoid framing; Delimitation detection
Physical Indicators	Rated voltage	DC12V 2A
	Power consumption	Rated power: 11.1 W (With IR LED lights ON)/ Max power: 16.6W
	Operating condition	Temperature: -10~50℃, Humidity: <90%
	Weight	Net:1540g Gross:2060g (Note: in kind prevail)
	Package size	280x230x155mm LxWxH