

Specifications Model: CS26Q

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/3 inch Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W mode)
	Lens	4.0mm
	View Angle	101° (diagonal)
	Night vision	The dual filter switches automatically, 2pcs 28mil patch IR LED IR irradiation distance:5~10m
Video	Encode format	H.264 main profile/Motion-JPEG/JPEG
	Resolution	5MP
	Bit rate/Frame rate/Display frequency	128~4096kbps/1~30pfs/60Hz、50Hz
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	RJ-45(10 / 100Base-T)
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~2.4835GHz; 5G
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 355°, tilt: 110°
	Preset position	PC APP: support 16 positions, Phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 256GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection, Humanoid detection, Humanoid tracking, Crying detection
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power: 2.8W(IR LED on), Maximum power: 4.3W (Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: 185 g Gross: 450 g(Note: in kind prevail)
	Package size	185x125x92 mm(L×W×H)