

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1 / 3 inch Progressive Scan CMOS
	Minimum Illumination	0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	Lens	4.0mm@F2.1
	View Angle	101° (diagonal)
	Night vision	Dual Filter,IR-Cut, 2pcs 28mil SMD IR LED IR irradiation distance:5~10m
Video	Encode format	H.264 main profile/Motion-JPEG/JPEG
	Resolution	2688x1520@30pfs/640*360@15pfs
	Bit Rate/FPS/Frequency	128~4096kbps/1~30pfs/60Hz、50Hz
	Image adjustment	Adjustable brightness and contrast
Audio	Input	Built-in -38 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4GHz、5 GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan-tilt	Pan-tilt	Pan: 350°,Tilt: 110°
	Preset position	PC client : support 16 positions, phone APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 256GB
Alarm	Alarm Trigger	Motion detection, Humanoid detection, Humanoid tracking, Cry detection
Physical Environmental	Rated voltage	DC 5V±5%
	Power consumption	Related power:2.3W(IR LED on), Maximum Power: 5.2W (Pan&Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net weight: 185g Gross weight: 450g(Note: in kind prevail)
	Package size	185x125x92 mm(L×W×H)