

Model: CS54-POE

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.1 Lux (B&W mode), 0.5 Lux (Color mode)
	Lens/Viewing angle	3.6mm@F2.0/97.2° Diagonal
	Night vision	IR-CUT with auto-switching, 8 pcs high-power 850nm patch IR LED lights(including 2 dual light source patches), IR LED and LED lights dual light sources (6pcs IR LED+ 4pcs LED lights); Irradiation distance: 15~20 m
Video	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1296p(2304×1296)@15fps/1080p(1920×1080)@30fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P, etc.
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud storage; NVR; NAS
Alarm	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid framing; Delimitation detection; Siren alarm
Physical Indicators	Rated voltage	DC12V 1A or POE (48V) power supply
	Power consumption	Rated power: 4.08W (with IR LED lights ON)/Max power: 4.44W
	Operating condition	Temperature: -10~50℃; Humidity: <90%
	Weight	Net: 280g (Note: in kind prevail)
	Package size	220x150x120mm (LxWxH)