

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.1 Lux (B&W mode), 0.5 Lux (Color mode)
	Lens/Viewing angle	3.6mm@F2.0/101° Diagonal
	Night vision	IR-CUT with auto-switching, 6 pcs IR +LED lights; 2 pcs red & blue alarm lights; Irradiation distance: 20~30 m
Video	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1296p(2304×1296)@15fps/1080p(1920×1080)@30fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud storage; NVR; NAS
Alarm	Alarm detection	Supports Delimitation detection; Humanoid framing; Humanoid detection; Alarm voice prompt, flashing & illumination; LED light timing ON & OFF
Physical Indicators	Rated voltage	DC12V±5% or POE (48V)
	Power consumption	Rated power: 4.1W (with IR LED lights ON)/Max power: 5W
	Operating condition	Temperature: -10~50℃; Humidity: <90%
	Weight	Net:350g (Note: in kind prevail)
	Package size	(230x190x108) mm (LxWxH)