

Model: CS65Q-X5

System	Operation system	Embedded Linux
	Online visitor	Support 4 visitors at the same time
Collection	Image sensor	1/3 inch Progressive Scan CMOS
	Minimum illumination	0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	Lens/View angle	3.5-9.5mm zoom lens/ 99.3~40.5°(Diagonal)
	Night vision	IR-CUT with automatic switching, 6 pcs 850nm IR LED lights(1 pcs blue alarm light and 1 pcs red alarm light) ; 6 pcs high-power LED lights, Irradiation distance:15-20 m
Video	Encode format	H.264 main profile/Motion-JPEG/JPEG
	Multiple streams	2688*1520@15fps /640*360@15fps
	Bit Rate/Max Fps	128~4096kbps/30pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built in -28±5dB microphone
	Output	Built in 8Ω2W speaker
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Pan/Tilt	Pan-tilt	Pan: 355°, Tilt: 95°
	Preset position	PC Client: support 16 positions, Mobile APP: support 5 positions
Memory	Storage function	Support TF card, Maximum support 256GB; Cloud Storage; NVR; NAS
Alarm	Alarm detection	Support Motion detection, Humanoid detection, Humanoid tracking
Physical Environmental	Rated voltage	DC12V 2A ±5%
	Power consumption	Rated power: 4.08W (with IR LED light on)/ Max power: 13.8W
	Operating condition	Temperature:-10~50℃,Humidity:<90%
	Weight	Net: 965g (Note: in kind prevail)
	Package size	205x195x130mm(L*W*H)