


CS665Q	4 MP, 2.5 inch Dome camera, (Dual antenna), Dual light source	
	Chip	Ingenic T31
	Sensor	GC4653
	Pixel	4MP/ 25fps
Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/3 inch 1440p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	4mm@F2.0/101°Diagonal
	Night vision	IR-CUT with auto-switching, 6PCS LED lights, 6PCS IR LED lights, Irradiation distance: 15~30 m
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1440p(2560×1440)@25fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
Image adjustment	Brightness and contrast are adjustable	
Audio	Input	Built-in — 38dB microphone
	Output	Built-in 8Ω2 W speaker
	Sampling frequency/bit	8KHz/16bit

Shenzhen VStarcam Technology Co., Ltd

	width	
	Compression standard/Bit Rate	G.711/64kbps
Network	Network interface	10Mbps/100Mbps auto-adaptive/RJ45 interface
	Network Protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P, etc.
Pan & Tilt	Pan & Tilt	Pan 350° /Tilt 90°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage,NVR; NAS
Alarm	Alarm detection	Support Motion detection, Humanoid detection, Humanoid tracking; Alarm voice prompts and flashing, irradiation functions, LED light timing ON & OFF
Physical Indicators	Rated voltage	DC12V
	Power consumption	Rated power: 4.5W (IR LED light on) / Maximum power: 11W (Pan & Tilt on)
	Operating condition	Temperature: -10~50°C; Humidity: <90%