

| | | |
|-----------------------|-------------------------------|--|
| | Selling points | <ol style="list-style-type: none"> 1. Wireless & wired connection, 3MP, 4 inch (Dual antenna) 2. Red and blue alarm lights 3. Dual light sources; Night vision: 30 m; 9 pcs LED lights, 6 pcs IR LED lights 4. Two-way talk; Pendant-mounted available; Rainproof & dustproof 5. Storage card recording supports up to 256G 6. Delimitation detection; Humanoid framing; Humanoid tracking; Humanoid detection alarm 7. LED light timing ON & OFF 8. Alarm voice prompt, flash & irradiation; Smoke alarm; Absence detection alarm |
| Sorts | Type | Parameters |
| System | Operating system | Embedded Linux |
| | Online visitor | Supports 4 visitors at the same time |
| | CPU/Image sensor | 1/2.9 inch 1080p progressive scan CMOS sensor |
| | Minimum illumination | 0.5 Lux (Color mode) , 0.1 Lux (B&W mode) |
| | Lens/Viewing angle | 3.6mm@F2.0/110°(Diagonal) |
| | Night vision | IR-CUT with auto-switching, 9 pcs LED lights, 6 pcs IR LED lights; Irradiation distance: 20~30 m |
| | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | Data Rate | Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps |
| | Bit rate/maximum frame rate | 128~4096kbps/30fps |
| | Image adjustment | Brightness and contrast are adjustable |
| Audio | Input | Built-in -38dB microphone |
| | Output | Built-in 8Ω2W speaker |
| | Sampling frequency/bit width | 8KHz/16bit |
| | Compression standard/Bit Rate | G.711/64kbps |
| Network | Network interface | 10Mbps/100Mbps adaptive /RJ45 |
| | Network protocol | TCP/IP, HTTP, TCP, UDP, DHCP, ONVIF,DNS, NTP, RTSP, P2P etc. |
| | Wireless network | IEEE802.11b/g/n; Supports AP mode |
| | Wireless frequency | 2.4GHz |
| | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| Pan & Tilt | Rotation angle | Pan 265° /Tilt 110° |
| | Preset position | Supports 16 (Mobile phone App only supports 5) preset |

| | | |
|----------------------------|---------------------|---|
| | | positions |
| Storage | Storage functions | Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS |
| Alarm | Alarm detection | Supports Motion detection; Humanoid detection; Humanoid tracking; Alarm voice prompt , flash & irradiation; LED light timing ON & OFF |
| Physical indicators | Rated voltage | DC12V±5% |
| | Power consumption | Rated power: 4.5W (with IR LED ON)/Max power: 11W (with Pan & Tilt ON) |
| | Operating condition | Temperature: -10~50°C, Humidity: <90% |
| | Weight | Net: 578g (Note: in kind prevail) |
| | Size | (230x205x140) mm |