

| | | |
|---------------|---|--|
| CS669 | 1.5 inch PT camera, 3 MP, dual light sources, red and blue alarm lights |  |
| | Chip | Ingenic T31 (N version) |
| | Sensor | GC2063 |
| | WiFi | BL-M5995NU1 |
| | Pixel | 3MP |
| | Brand | VSTARCAM |
| | | |
| Sorts | Type | Parameters |
| System | Operating system | Embedded Linux |
| | Online visitor | Supports 4 visitors at the same time |
| | CPU/Image sensor | 1/2.9 inch 1080p progressive scan CMOS sensor |
| | Minimum illumination | 0.5 Lux (Color mode) , 0.1 Lux (B&W mode) |
| | Lens/Viewing angle | 4mm@F2.3/101°(Diagonal) |
| | Night vision | IR-CUT with auto-switching, 4 pcs LED lights, 6 pcs IR LED lights; Irradiation distance: 20~30 m |
| | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | Data Rate | Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps |

Shenzhen VStarcam Technology Co., Ltd

| | | |
|----------------------------|-------------------------------|---|
| | | Substream: 360p(640×360)@15fps |
| | Bit rate/maximum frame rate | 128~4096kbps/30fps |
| | Image adjustment | Brightness and contrast are adjustable |
| Audio | Input | Built-in -38dB microphone |
| | Output | Built-in 8Ω2W speaker |
| | Sampling frequency/bit width | 8KHz/16bit |
| | Compression standard/Bit Rate | G.711/64kbps |
| Network | Network interface | 10Mbps/100Mbps adaptive /RJ45 |
| | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc. |
| | Wireless network | IEEE802.11b/g/n; Supports AP mode |
| | Wireless frequency | 2.4~2.4835GHz |
| | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| Pan & Tilt | Pan & Tilt | Pan 263° /Tilt 90° |
| | Preset position | Supports 16 (Mobile phone App only supports 5) preset positions |
| Storage | Storage functions | Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS |
| Alarm | Alarm detection | Supports Motion detection; Humanoid detection; Humanoid tracking; Alarm voice prompt , flash & irradiation; LED light timing ON & OFF |
| Physical indicators | Rated voltage | DC12V±5% |
| | Operating condition | Temperature: -10~50℃, Humidity: <90% |
| | Weight | (Note: in kind prevail) |