


<p><b>CS880-POE</b> <b>Dome camera</b></p>	<p><b>3MP, Dome camera, dual light sources</b></p>	
	<p><b>Chip</b></p>	<p><b>Ingenic T31</b></p>
	<p><b>Sensor</b></p>	<p><b>HD</b></p>
	<p><b>Pixel</b></p>	<p><b>3MP</b></p>
	<p><b>Brand</b></p>	<p><b>VSTARCAM</b></p>
	<p><b>Selling points</b></p>	<ol style="list-style-type: none"> <li><b>1. Wired connection, 3MP, Dome camera</b></li> <li><b>2. Dual light source Night vision 10-20 meters, 4PCS dual light sources lights(LED light + IR LED light)</b></li> <li><b>3. Two-way talk, Hoisting installation available</b></li> <li><b>4. Maximum support TF card 256G,</b></li> <li><b>5. Delimitation detection, Humanoid framing, Humanoid detection alarm,</b></li> <li><b>6. LED light timing ON &amp; OFF</b></li> <li><b>7. Support Motion detection, Humanoid detection;</b></li> </ol>
<p><b>Sorts</b></p>	<p><b>Type</b></p>	<p><b>Parameters</b></p>
<p><b>System</b></p>	<p>Operating system</p>	<p>Embedded Linux</p>
	<p>Online visitor</p>	<p>Supports 4 visitors at the same time</p>
	<p>CPU/Image sensor</p>	<p>1/3 inch 1080p progressive scan CMOS sensor</p>
	<p>Minimum illumination</p>	<p>0.5 Lux (Color mode) , 0.1 Lux (B&amp;W mode)</p>
	<p>Lens/Viewing angle</p>	<p>3.6mm@F2.0/101° Diagonal</p>
	<p>Night vision</p>	<p>IR-CUT with auto-switching , 4PCS dual light sources(LED lights+ IR LED lights); Irradiation distance: 10~20 m</p>
	<p>Compression standard</p>	<p>H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG</p>
	<p>Data rate</p>	<p>Main stream:1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps</p>
	<p>Bit rate/maximum frame</p>	<p>128~4096kbps/30fps</p>
	<p>Image adjustment</p>	<p>Brightness and contrast are adjustable</p>



My safety, My rule!

## Model: CS880-POE

<b>Audio</b>	Input	Built-in -38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
<b>Network</b>	Network interface	10Mbps/100Mbps adaptive /RJ45 interface support POE
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
<b>Storage</b>	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS
<b>Alarm</b>	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid tracking, LED light Timing ON/OFF
<b>Physical Indicator</b>	Rated voltage	DC12V±5%
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	Net weight: 216g (Note: in kind prevail)
	Package size	165*160*125mm (LxWxH) (Note: in kind prevail)

Shenzhen VStarcam Technology Co., Ltd

[www.vstarcam.com](http://www.vstarcam.com)