

Model: BG69

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0. 1 Lux(B&W mode)
	Lens/Viewing angle	4mm@F2.0/ 107°Diagonal
	Night vision	IR-CUT with auto-switching, 6PCS IR LED lights; Irradiation distance: 10~ 15 m
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1296p(2304× 1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in — 38d B microphone
	Output	Built-in 8Ω2 W speaker
	Sampling frequency/bit width	8KHz/ 16bit
	Compression standard/Bit Rate	G.711/64kbps
Network	4G LTE (Chinese version)	FDD: B1/ B3/ B5/ B8 TDD:B34/B38/B39/ B40/ B41
	4G LTE (European version)	LTE- FDD: B1/B3/ B7/ B8/ B20 LTE-TDD: B40/ B41
Pan & Tilt	Pan & Tilt	Pan 345° /Tilt 55°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T- Flash card(max supports 256GB); Cloud Storage
A larm	Alarm detection	Humanoid detection
Physical Indicators	Rated voltage	DC5V±5%
	Power supply	Supports four 18650 or four 21700 batteries
	Power consumption	Rated power: 5W (with IR LED lights ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: - 10~50C; Humidity: < 90%
	Weight	(Note: in kind prevail)